

# **SAFETY DATA SHEET (SDS)**

Section 1: IDENTIFICATION							
TRADE NAME	Gebauer's Pain Ease <sup>®</sup>	MANUFACTURER	Gebauer Company 4444 East 153 Street Cleveland, Ohio 44128				
CHEMICAL NAME	1,1,1,3,3-Pentafluoropropane 1,1,1,2-Tetrafluoroethane	CONTACT INFORMATION	Toll Free: (800) 321-9348 Phone: (216) 581-3030 Fax: (216) 581-4970				
RECOMMENDED USE	Topical Anesthetic	IN CASE OF EMERGENCY	CHEMTREC - (800) 242-9300 or (703) 527-3887				
FORMULA	CHF <sub>2</sub> CH <sub>2</sub> CF <sub>3</sub> / CH <sub>2</sub> FCF <sub>3</sub>	CHEMICAL FAMILY	Halogenated Hydrocarbon				

# **Section 2: HAZARDS IDENTIFICATION**

Health Rating Flammability Rating Reactivity Rating Special Rating

2 - Moderate0 - None1 - Moderate

Lab Protective Equipment

None
Neoprene or Viton gloves, lab coat, goggles or face shield, vent hood.

, , , , , ,							
Hazard Category	Signal Word	Hazard Statement	Pictogram	Precautionary Statement			
Compressed Gas Warning		Contains gas under pressure; may explode if heated		Store is a well-ventilated place.			
Eye Irritation (Category 2B)	Warning	Causes eye irritation	N/A	If product gets into eyes, see the Section 4: First Aid Measures.			
Cause		Effects					
	Inhalation	When oxygen levels in air are reduced to 12-14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.					
Potential Acute Health Effects	Ingestion	Unlikely route of exposure due to gaseous nature. Discomfort due to volatility would be expected.					
	Eye Contact	Liquid contact can cause irritation and frostbite.					
	Skin Contact	Over application could cause frostbite. Liquid contact is non-irritating.					

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS								
Ingredient	CAS Number	Concentration	OSHA PEL	ACGIH TLV-TWA				
1,1,1,3,3-Pentafluoropropane	460-73-1	95%	None	None				
1,1,1,2-Tetrafluoroethane	811-97-1	5%	None	None				

# Inhalation | Impediately remove patient to fresh air. If breathing has stopped, give artificial respiration. Use oxygen as required, provided a qualified operator is available. Do NoT give epinephrine (adrenaline). Get medical attention immediately. | Ingestion | Unlikely route of exposure due to gaseous nature. Do NoT induce vomiting unless instructed to do so by a physician. Do NoT give stimulants. Get medical attention immediately. | Skin Contact | If there is evidence of frostbite seek medical attention.

Immediately flush eyes with copious amounts of water for at least 15 minutes (in case of frostbite water should be lukewarm, not hot) lifting lids occasionally

# Eye Contact Immediately flush eyes with copious amounts of water for at least 15 m to facilitate irrigation. Get medical attention.

### **Special Fire Fighting Procedures**

Fire fighters should wear self-contained, NIOSH approved breathing apparatus for protection against possible toxic decomposition products. Proper eye and skin protection should be provided. Use spray to keep fire-exposed containers cool.

**Section 5: FIRE FIGHTING MEASURES** 

## **Unusual Fire and Explosion Hazards**

Not flammable at ambient temperatures and atmospheric pressure. However this material will become combustible when mixed with air under pressure and exposed to strong ignition sources contact with certain reactive metals may result in formation of explosive or exothermic reactions under specific conditions (e.g. very high temperatures and/or appropriate pressures).

# Section 6: ACCIDENTAL RELEASE MEASURES

### Spill and Leak Response

If a large quantity of containers the product has been released, evacuate unprotected personnel. Protected personnel should eliminate all sources of ignition and shut off leak, if without risk, and provide ventilation.

# **Waste Disposal Method**

Comply with federal, state and local laws.

### **Section 7: HANDLING AND STORAGE**

### **Storage Precautions**

Store in cool, dry, well ventilated area of low fire risk. Protect against physical damage. Do not subject to temperatures above 120°F (50°C)

### **Handling Precautions**

**Respiratory Protection** 

Use in well-ventilated areas. Do not use near temperatures above 120°F (50°C)

### Section 8: EXPOSURE CONTROLS - PERSONAL PROTECTION

**Engineering Controls** Provide local ventilation at filling zones and where leakage is probable. Use with adequate ventilation.

None generally required for adequately ventilated work situations. For accidental release in confined space, where the concentration may be above the PEL of 1,000 ppm, use a NIOSH approved, self contained, positive pressure respirator for emergencies and in situations where air may

be displaced by vapors.

Use protective, impervious gloves and clothing made of neoprene, nitrile or butyl rubber if prolonged or repeated contact with liquid is anticipated. **Skin Protection** Wash clothing promptly, if wet. Remove any non-impervious clothing and wash before re-use.

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles. **Eye Protection** 

Contact lenses should not be worn under such conditions.

OSHA PEL: None **Exposure Limits** ACGIH TLV: None

# Section 9: PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point:** 44.6°F (7.0°C) Vapor Pressure (@72°F): 10.8 psig Flash Point None

Flammable Limits in Air: **Evaporation Rate:** >1 Specific Gravity (@72°F): 1.33 Nonflammable

(Carbon Tetrachloride = 1) (by Volume)

Air=1 BP 4.7 Colorless Liquid Odor: Vapor Density: Appearance: Faint Ethereal, Sweet

# Section 10: STABILITY AND REACTIVITY

Stability Product is stable under normal conditions.

**Hazardous Decomposition** Halogens and halogen acids; and possibly carbonyl halides. **Products** 

Strong acids and alkalis, reactive metals e.g., powdered or freshly abraded aluminum (may cause strong exothermic reaction), sodium, **Incompatible Materials** 

potassium, calcium, magnesium, zinc, molten aluminum, barium and lithium shavings. Strong oxidizing agents.

**Hazardous Polymerization** Does not occur.

> Avoid sources of ignition such as sparks, hot spots, welding flames and lighted cigarettes which may yield toxic and/or corrosive decomposition **Conditions to Avoid** products. Do not mix with oxygen or air above atmospheric pressure.

# Section 11: TOXICOLOGICAL INFORMATION

**Dermal Irritation** Non-irritation and not a skin sensitizer. Eye Irritation Very slight irritant.

Inhalation Evidence of transient anesthetic effect. 1,1,1,2-Tetrafluoroethane: Lowest observed adverse effect level for cardiac sensitization was 75,000ppm.

### Section 12: ECOLOGICAL INFORMATION

**Environmental Stability** 

Gas is dissipated rapidly in a ventilated area.

CAS 40-73-1: Acute Toxicity to Rainbow Trout (Limit Test): NOEC >10 mg/L; 96 hr. EC<sub>50</sub>>8108 mg/L Effect on Aquatic Life

CAS 811-97-1: Acute Toxicity to Rainbow Trout (Limit Test): 96 hr. LC50 is 450 mg/L

# Section 13: DISPOSAL CONSIDERATIONS

Waste disposal must be in accordance with appropriate Federal, State and local regulations.

# **Section 14: TRANSPORT INFORMATION**

**UN Number** UN 3163 **Proper Shipping Name** Liquefied Gas, N.O.S (1,1,1,3,3-Pentafluoropropane, 1,1,1,2-Tetrafluoroethane) DOT Class 2.2, Non-Flammable Gas

> **Hazard Label** Limited Quantities

**UN Number** UN 3163

> **Proper Shipping Name** Liquefied Gas, N.O.S (1,1,1,3,3-Pentafluoropropane, 1,1,1,2-Tetrafluoroethane)

> > Class 2.2. Non-Flammable Gas

**Hazard Label** Air-Specific Limited Quantities

### **REGULATORY INFORMATION** Section 15:

**USA TSCA Europe EINECS** Not Listed

IATA

SARA Tittle III RQ's and EHS TPQ: Not Listed. Sections 311, 312: Not Listed

WHMIS Classification (Canada) SDS meets requirements of SPR **European Union** Not Listed as Hazardous Substance

Contains greenhouse gases, which may contribute to global warming. Regulated in the US under Section 612 (SNAP) of the Clean Air Act and 40 Additional Regulatory Information CFR Part 82, subpart G.

# **Section 16: OTHER INFORMATOIN**

This SDS was revised and updated as of 12/08/2022 by Gebauer Company.

Y QUALIFIED PERSONNEL AT THEIR DISCRETION AND RISK. ALL STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED H OF IS NOT GUARANTEED AND NO WARRANTY OF ANY KIND IS MADE WITH RESPECT THERETO. THIS INFORMATION IS NOT INTENDED AS A LICENSS HER COVERING ANY PROCESS, COMPOSITION OF MATTER OR USE. SINCE THE COMPANY SHALL HAVE NO CONTROL OF THE USE OF THE PRODUC